SoyIt™

Concrete-Masonry Graffiti Remover

TECHSHEET

EnvirotekCorporation
Ultimate Surface Cleaners

PRODUCT DESCRIPTION

SoyIt™ is a concrete-masonry graffiti remover, that is a highly effective, cost effective, biodegradable and designed to remove: tuff aerosol spray-paints, specialized graffiti paints, heavy-duty primers, inks, markers, wax-crayons and more. From porous: brick, stone and most concrete surfaces including cinder-block, split-face block and exposed aggregate. All raw martial can be found on the EPA Safer Choice ingredients list. **SoyIt**™ helps restore and revitalizes the natural substrate.

MAIN FEATURES

- **SoyIt**™ works fast & effectively to remove graffiti in one application.
- **SoyIt**™ Removes graffiti, is non-damaging, and helps restore the natural surface.
- **SoyIt**™ outperforms the competition
- **SoyIt**™ works on a wide array of concrete-masonry surface, such as slip-face, cinder-block, natural stones, and more
- Save time and save money with **SoyIt**™

TECHNICAL DATA

pH: 11.5-12.555
Flash Point: 211°F
Coverage: 350 - 450 sq. ft./gallon.
Shelf Life: 3-5 years (depending on temp and storage)
VOC: 30% or less

RECOMMENDED SUBSTRATES

SoyIt™ concrete-masonry surface, graffiti remover, is recommended for use on unpainted-uncoated: concrete-masonry, stone, brick, pavers, cinderblock, split-face, granite, marble, title and most cementation surfaces. Not for use on: signs, metals, plexiglass, fiberglass, most forms of plastics, plywood, drywall, or most smooth-sensitive surfaces. Always test small area before using product.

GENERAL APPLICATION

SoyIt™ recommend application with spray or brush/ broom. Apply **SoyIt**™ 1-2, flood coat graffiti-tagged surface. Agitation graffiti tagged areas with brush or broom, as you apply **SoyIt**™ Always, keep the graffiti-tagged soaked with the product, as long as possible before rinsing. Alway pressure-wash for bottom-top, lowest point - highest point.

CONCRETE-MASONRY

When removing graffiti on concrete (such as; side-walks, pour-in-place wall, etc), spray **SoyIt**™ directly onto graffiti-tagged area. Use brush or broom to agitated graffiti. Apply **SoyIt**™ 2-3times in a 5-10mins, saturate surface with **SoyIt**™, do not allow surface to dry-out.

BRICK, CIDER-BLOCK, SPLIT-FACE

Application of water, before applying **SoyIt**™ may help insure maximum results. Brick, cinder-block, and split-face, rapidly absorbs graffiti-cleaners more so, then other surfaces. Flood graffiti-tagged area, with water before applying **SoyIt**™ Then apply **SoyIt**™ to graffiti-tagging.

SUNBAKED OR AGED-GRAFFITI

With highly sunbaked or aged-graffiti, apply, at least 3 times, allow a dwell time of 15-20mins (and in some cases longer). Do not allow surface to dry-out, keep area saturated with **SoyIt**™

FOR INDUSTRIAL USE ONLY. UN#2924. POTASSIUM HYDROXIDE 1310-58-3. AS DIRECTED. FOR EXTERIOR/OUTDOOR USE ONLY.MANUFACTURER NOT RESPONSIBLE FOR DAMAGE OR INJURY. PRODUCT MAY CAUSE DAMAGE TO SURFACE. NOT FOR USE ON CHILDREN'S PLAY EQUIPMENT.

More Info: support@envirotekcorporation.com
Website: www.envirotekgraffiti.com
Local Sales Rep: 818.793.2323

EnvirotekCorporation
Ultimate Surface Cleaners

MADE IN USA